



ENVHYROMAT

EnvhyroMat panels are mainly used to create temporary accesses, car parks and temporary platforms...

They can be laid on different types of surface whether already partially or fully installed. Weighing only 35 kg, EnvhyroMat panels are easily hand-installed by 2 people.

Thanks to their design and robustness, they have an permissible load of up to 80 tons / m².



Technical specifications

- **Material:** 100% recycled or virgin high density polyethylene (PEHD)
- **Colour:** Black
- **Surface:** Non-slip profile
- **Dimensions :** 2.89 m²/panel - 2.41 m x 1.20 m x 12 mm
- **Poids :** 35 kg/panel
- **Charge admissible :** 80 t/m² depending on the type of ground
- **Transport :** 30 panels / pallet and 22 pallets per articulated lorry, ie 1 907 m².

Properties

- Solid one-piece construction.
- The panels can be connected to each other by 2 and 4-way connectors.
- These panels are ideal for events, concerts, festivals and building sites.
- They allow accessibility to pedestrians, persons of reduced mobility, light and heavy goods vehicles.



WOULD YOU LIKE MORE INFORMATION? A QUOTE OR AN ESTIMATE?



Adviser Envhyro
+33 3 86 98 00 79
contact@envhyro.com



Website
www.envhyro.fr