



PLAQ'ECO

PLAQ'ECO panels are mainly used for temporary access.

They can be laid on different types of surface whether already partially or fully installed. They have a permissible load of up to 45 tons / m².

Weighing only 60 kg, the PlaQ'Eco panels are easily hand-installed by 2 people.



Technical specifications

- **Material:** 100% recycled or virgin high density polyethylene (PEHD)
- **Colour:** Black
- **Surface:** Non-slip profile
- **Dimensions:** 3 m²/panel - 3.00 m x 1.00 m x 15 mm or 3.00 m x 1.00 m x 20 mm
- **Weight:** 45 kg/panel (15 mm) - 60 kg/panel (20 mm)
- **Permissible:** 45 tonnes / m² (15 mm) - 60 tonnes / m² (20 mm) depending on the type of ground
- **Transport :** 25 panels / rack (15 mm), 20 panels / rack (20 mm) and 16 racks per articulated lorry, ie 1200 m² (15mm) and 1080 m² (20 mm)

Properties

- Solid one-piece construction.
- The panels can be connected to each other with quick-connect couplings.
- These panels are versatile and can be used for events, concerts, festivals and construction sites.
- They allow accessibility to pedestrians, people with reduced mobility, light and heavy-goods vehicles and construction equipment.

WOULD YOU LIKE MORE INFORMATION? A QUOTE OR AN ESTIMATE?



Adviser Envhyro
+33 3 86 98 00 79
contact@envhyro.com



Website
www.envhyro.fr